



Micro Sensors

Mini Sensor

LEL Sensor

## SST5

FIVE-GAS DETECTOR



### RTR COMPATIBLE

#### Applications

- Oil and gas upstream
- Steel production
- Wastewater
- Ship building
- First responders
- Manufacturing
- Shipping
- Power generation

## Features and Benefits



### NFC

Near Field Communication built in as standard and allows for a wide range of solutions depending on your needs. Simply pair SST5 with the WatchGas Device Link App to manage your fleet, bump, calibrate, assign, or download event logs. See Tap & Go application note for more information on the benefits of NFC and what it can do for you.



### Rugged

Designed with the harshest environments in mind the SST5 offers an IP rating of 65/68. The casing is a double shot housing that gives extra robustness whilst not compromising on quality. The screen protectors located either side of the display are to protect the LCD from scratching and is required due to the smaller sensor profile.



### Alert

As a safety device, the SST5 ensures users are immediately and clearly notified of the presence of gas. It features one of the loudest alarms in its category, delivering a powerful 95 dB at 30 cm, making it highly audible even in the noisiest industrial environments. High, Low, STEL and TWA alarms can be configured by the user and are automatically updated directly on the device or through the SST Dock or WatchGas Device Link App, providing reliable, customizable, and highly effective protection at all times.



### Display

With a great screen-to-product size ratio and one of the largest screens in its category, the SST5 display ensures information is displayed clearly and allows users to make quick decisions. Up to five gases can be shown simultaneously, toxic in mg/m<sup>3</sup> or PPM and explosive in %LEL or %VOL. Correction factors can be set through the WatchGas Device Link App, allowing a one-to-one reading for the target gas required. The backlight enables use in dark environments and automatically illuminates during an alarm event.



### Sensor

Using the latest micro sensor technology for H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub> and traditional electrochemical sensors for exotic gases. The SST5 offers 2 HCN types (filtered and unfiltered), as well as an Xs broadband sensor for general application, and for a 5th target gases.



### Innovation

In dirty and harsh environments that gas detectors are often used in many charging connectors become damaged. SST5 has been designed with induction charging allowing for simple and quick charging with no risk of cables and ports becoming damaged and failing.

The SST5 is one of the smallest and lightest 5-gas monitors on the market, easily worn in the breathing zone. It is typically around 40% smaller and 25% lighter than other 5-gas diffusion portable detectors, offering exceptional comfort and flexibility for users. Despite its compact size, the rugged SST5 is built to perform in a wide range of environments, from the high temperatures of the steel industry to the challenging conditions faced by Hazmat teams or the extreme environments of the Oil and Gas sector. With a broad range of configurable options, the SST5 can be tailored to suit diverse applications. Simple setup, calibration, and bump test records are easily managed through the WatchGas Device Link App, while compliance checks make it straightforward to maintain your devices and ensure maximum uptime across your fleet.

### SST5 SPECIFICATIONS


<b>Size</b>	107.9 x 62.4 x 26.1 mm / 4.2 x 2.4 x 1.0 in
<b>Weight</b>	188 g / 6.6 oz.
<b>Temperature</b>	H <sub>2</sub> S, CO, O <sub>2</sub> & SO <sub>2</sub> : -40 ~ +60 °C / -40 ~ +140 °F Others: -20 to +50°C / -4 to +122°F LEL: -40 to +60°C / -40 to +140°F
<b>Humidity</b>	5 ~ 95% r.h. (non-condensing)
<b>Typical battery life</b>	SST5 LEL LPC (Low Power Catalytic) - 48hr SST5 LEL NDIR (Non Dispersive Infrared) - 200hr
<b>Induction charger</b>	2 to 3 hours
<b>Event logging</b>	100 events
<b>Data logging</b>	6 months
<b>IP</b>	65/68
<b>Communication</b>	NFC
<b>Calibration</b>	6 month as standard
<b>Certifications and approvals</b>	<p><b>Ex</b> ATEX, IECEx, UKEX : LEL-LPC II 1 G Ex ia IIC T4 Ga, I M1 Ex ia I Ma LEL-IR II 1 G Ex ia op is IIC T4 Ga, I M1 Ex ia op is I Ma</p> <p><b>MET</b> North America: (non-IR) Class I Division 1 Group A,B,C,D T4 U.S. Canada Class I Zone 0 AEx ia IIC T4 Ga Ex ia IIC T4 Ga</p> <p>North America: (IR) Class I Division 1 Group A,B,C,D T4 U.S. Canada Class I Zone 0 AEx ia op is IIC T4 Ga Ex ia op is IIC T4 Ga</p> <p><b>CE</b> EMC Directive 2014/30/EU</p> <p>(PESO) Ex ia IIC T4 Ga Ex ia op is IIC T4 Ga (with IR sensor)</p> <p><b>KCS</b> (Korea) Ex ia IIC T4 Ex ia op is IIC T4 (with IR Sensor)</p> <p><b>ATEX</b> Ex ia I Ma, Ex ia IIC T4 Ga Ex ia op is I Ma, Ex ia op is IIC T4 Ga (with IR sensor)</p> <p><b>ATEX</b> (ABS Type Approved) 24-00T2542343-1-PDA</p>
<b>Warranty</b>	Instrument and O <sub>2</sub> , LEL, CO, H <sub>2</sub> S, SO <sub>2</sub> Sensors: 2 years Other sensors: 1 year

### SENSOR SPECIFICATIONS


Sensor type	Gas measuring range	Low alarm	High alarm	STEL	TWA	Resolution
<b>Micro Sensors</b>						
H <sub>2</sub> S	0 - 500 ppm	10 ppm	15 ppm	15 ppm	10 ppm	0.1 ppm
CO	0 - 2000 ppm	35 ppm	200 ppm	100 ppm	20 ppm	1 ppm
O <sub>2</sub>	0 - 30% Vol.	19.5% Vol.	23.5% Vol.	N/A	N/A	0.1% Vol.
SO <sub>2</sub>	0 - 100 ppm	5 ppm	10 ppm	5 ppm	2 ppm	0.1 ppm
<b>Mini Sensors</b>						
Cl <sub>2</sub>	0 - 50 ppm	0.5 ppm	1 ppm	1 ppm	0.5 ppm	0.1 ppm
ETO	0 - 100 ppm	5 ppm	10 ppm	10 ppm	5 ppm	0.1 ppm
HCN (unfiltered)	0 - 50 ppm	5 ppm	10 ppm	4 ppm	4 ppm	0.1 ppm
HCN F*	0 - 50 ppm	5 ppm	10 ppm	4 ppm	4 ppm	0.1 ppm
NH <sub>3</sub>	0 - 100 ppm	25 ppm	50 ppm	35 ppm	25 ppm	0.1 ppm
NO	0 - 100 ppm	25 ppm	50 ppm	50 ppm	25 ppm	0.1 ppm
NO <sub>2</sub>	0 - 20 ppm	2 ppm	5 ppm	5 ppm	3 ppm	0.1 ppm
SO <sub>2</sub>	0 - 40 ppm	5 ppm	10 ppm	5 ppm	2 ppm	0.1 ppm
Xs**	0 - 100 ppm	25 ppm	50 ppm	50 ppm	25 ppm	0.1 ppm
<b>LEL Sensors</b>						
LPC	0 - 100% LEL	10%	20%	N/A	N/A	1% LEL
NDIR	0 - 100% LEL	10%	20%	N/A	N/A	1% LEL

All alarm levels can be set using the WatchGas Device Link App or SST Dock.  
\*Hydrogen Cyanide sensor with an integrated H<sub>2</sub>S filter to eliminate cross interference.  
\*\* High-stability broad-band sensor for certain organic gases and vapors.


### Accessories




**Universal Cradle Charger for SST Range**  
SST-IND-S



**WatchGas SST Range 5-Way Stackable Charging Cradle**  
SST-STACK-CHR



**SST Dock**  
SST-DOCK



**WatchGas SST RTR Web Reporting Software**  
SST-SOFTWARE

Distributed by:

#### For more information

www.watchgas.com / www.watchgasusa.com  
info@watchgas.com / info@watchgasusa.com

#### WatchGas SST5 DS EN V2.1 E7F © 2026 WatchGas B.V.

WatchGas is dedicated to continuously improving its products. Therefore, the specifications and features mentioned in this datasheet are subject to change without prior notice.